

1. GENERAL INFORMATION	
1.1	Date updated: Jul 22, 2020
1.2	Vessel's name (IMO number): Ottoman Courtesy (9788708)
1.3	Vessel's previous name(s) and date(s) of change: Not Applicable
1.4	Date delivered/Builder (where built): Aug 16, 2017/HHI Ulsan S.Korea
1.5	Flag/Port of Registry: Turkey/Istanbul
1.6	Call sign/MMSI: TCA4455/271044691
1.7	Vessel's contact details (satcom/fax/email etc.): Tel: +870 773 993 065 Fax: Email: courtesy@gungen.com.tr
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOPPC): Oil Tanker
1.9	Type of hull: Double Hull
<b>Ownership and Operation</b>	
1.10	Registered owner - Full style: GUNGEN DENIZCILIK VE TICARET ANONIM SIRKETI HALICI SOKAK NO.9 GOP ANKARA/TURKEY Tel: +90(312) 455 35 35 Fax: +90 (312) 455 35 25 Telex: 44111 or 44666 Email: vetting@gungen.com
1.11	Technical operator - Full style: Same as above Same as Q1.20.1 Tel: +90(312) 455 35 35 Fax: +90(312) 455 35 35 Telex: 44111 or 44666 Email: vetting@gungen.com Company IMO#: 1366389
1.12	Commercial operator - Full style: Same as Above
1.13	Disponent owner - Full style: N/A
<b>Insurance</b>	
1.14	P & I Club - Full Style: UK P&I CLUB 90 Fenchurch Street London EC3M 4ST Tel: 0044 020 7283 4646 Email: underwriting.ukclub@thomasmiller.com
1.15	P & I Club pollution liability coverage/expiration date: 1,000,000,000 US\$ Feb 20, 2021
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter) Willis Limited 51 Lime Street London EC3M 7DQ United Kingdom Telephone: +44 (0)2031246000 Fax: +44 (0)2031248223 Website: www.willis.com
1.17	Hull & Machinery insured value/expiration date: 110,000,000 US\$ May 20, 2021
<b>Classification</b>	
1.18	Classification society: DNV GL28741F97-5E94-4B05-ABE4-AFB4B01F4EA3
1.19	Class notation: 1A1 Tanker for oil BIS BMON BWM(T, E(s, f)) CCO Clean COAT-PSPC(B; C) CSR E0 ECA(SOx-A) ESP OPP-F Recyclable SPM TMON VCS(2, B)
1.20	Is the vessel subject to any conditions of class, class extensions, outstanding memorandums or class recommendations? If yes, give details: No N/A
1.21	If classification society changed, name of previous and date of change: , Not Applicable
1.22	Does the vessel have ice class? If yes, state what level: No, N/A
1.23	Date/place of last dry-dock: Aug 16, 2017/
1.24	Date next dry dock due/next annual survey due: Aug 16, 2022 Aug 16, 2019
1.25	Date of last special survey/next special survey due: Aug 16, 2017
1.26	If ship has Condition Assessment Program (CAP), what is the latest overall rating: No,
<b>Dimensions</b>	

1.27	Length overall (LOA):		269.08 Metres	
1.28	Length between perpendiculars (LBP):		258 Metres	
1.29	Extreme breadth (Beam):		46.04 Metres	
1.30	Moulded depth:		25.10 Metres	
1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in collapsed condition, if applicable:	57.175 Metres	49.60 Metres	
1.32	Distance bridge front to center of manifold:		91.13 Metres	
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):	132.89 Metres	136.19 Metres	
1.34	Parallel body distances	Lightship	Normal Ballast	Summer Dwt
	Forward to mid-point manifold:	59.21 Metres	59.56 Metres	68.10 Metres
	Aft to mid-point manifold:	45.76 Metres	46.98 Metres	67.50 Metres
	Parallel body length:	104.975 Metres	106.53 Metres	135.60 Metres

#### Tonnages

1.35	Net Tonnage:		47,745	
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):	83,537	67,730	
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):	86,205.32	82,230.81	
1.38	Panama Canal Net Tonnage (PCNT):		79,296	

#### Loadline Information

1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	7.55 Metres	17.59 Metres	149,999 Metric Tonnes	176,527.60 Metric Tonnes
	Winter:	7.55 Metres	17.59 Metres	149,999 Metric Tonnes	176,527.60 Metric Tonnes
	Tropical:	7.55 Metres	17.59 Metres	149,999 Metric Tonnes	176,527.60 Metric Tonnes
	Lightship:	22.16 Metres	3.24 Metres	-	26,528.60 Metric Tonnes
	Normal Ballast Condition:	17.21 Metres	9.85 Metres	47,954.10 Metric Tonnes	73,654.10 Metric Tonnes
	Segregated Ballast Condition:	17.22 Metres	7.90 Metres	47,905.50 Metric Tonnes	73,605.50 Metric Tonnes
1.40	FWA/TPC at summer draft:			397 Millimetres	111.09 Metric Tonnes
1.41	Does vessel have multiple SDWT? If yes, please provide all assigned loadlines:			No N/A	
1.42	Constant (excluding fresh water):			260 Metric Tonnes	
1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?			1-OCEAN AND OPEN WATERS: %15 OF SUMMER DRAUGHT 2-PORT LIMITS, APPROACHES, FAIRWAYS, CHANNELS, CANALS, RIVERS, SBM/CBM, WHILE ALONGSIDE: 1.5% OF MOULDED BREADTH OF THE VESSEL BUT NOT LESS THAN 0.7 METERS	
1.44	What is the max height of mast above waterline (air draft)			Full Mast	Collapsed Mast
	Summer deadweight:			39.585 Metres	32.01 Metres
	Normal ballast:			47.795 Metres	40.22 Metres
	Lightship:			53.935 Metres	46.36 Metres

2.	CERTIFICATES	Issued	Last Annual	Last Intermediate	Expires
2.1	Safety Equipment Certificate (SEC):	Oct 31, 2018	Sep 30, 2019	Aug 16, 2017	Aug 16, 2022
2.2	Safety Radio Certificate (SRC):	Oct 31, 2018	Sep 30, 2019		Aug 16, 2022
2.3	Safety Construction Certificate (SCC):	Oct 31, 2018	Sep 30, 2019	Aug 16, 2017	Aug 16, 2022
2.4	International Loadline Certificate (ILC):	Oct 31, 2018	Sep 30, 2019		Aug 16, 2022
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Mar 25, 2019	Sep 30, 2019	Aug 16, 2017	Aug 16, 2022
2.6	International Ship Security Certificate (ISSC):	Feb 05, 2018	Not Applicable	Not Applicable	Feb 05, 2023
2.7	Maritime Labour Certificate (MLC):	Feb 10, 2018	N/A		Feb 09, 2023
2.8	ISM Safety Management Certificate (SMC):	Feb 10, 2018	Not Applicable	Not Applicable	Feb 09, 2023
2.9	Document of Compliance (DOC):	Jun 18, 2019			Apr 05, 2021
2.10	USCG Certificate of Compliance (USCGCOC):		Not Applicable		
2.11	Civil Liability Convention (CLC) 1992 Certificate:	Jan 15, 2020	N/A	N/A	Feb 20, 2021

2.12	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Jan 15, 2020	N/A	N/A	Feb 20, 2021
2.13	Liability for the Removal of Wrecks Certificate (WRC):	Feb 21, 2020	N/A	N/A	Feb 20, 2021
2.14	U.S. Certificate of Financial Responsibility (COFR):	Sep 12, 2017	N/A	N/A	Sep 12, 2020
2.15	Certificate of Class (COC):	Oct 15, 2019	Sep 30, 2019	Aug 16, 2017	Jun 18, 2022
2.16	International Sewage Pollution Prevention Certificate (ISPPC):	Dec 07, 2017	N/A	N/A	Aug 16, 2022
2.17	Certificate of Fitness (COF):	Not Applicable	Not Applicable		Not Applicable
2.18	International Energy Efficiency Certificate (IEEC):	Oct 31, 2018	N/A	N/A	N/A
2.19	International Air Pollution Prevention Certificate (IAPPC):	Dec 07, 2017	Sep 30, 2019	Dec 07, 2017	Aug 16, 2022

#### Documentation

2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:		Yes
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?		Yes
2.22	Is the ITF Special Agreement on board (if applicable)?		N/A
2.23	ITF Blue Card expiry date (if applicable):		

### 3. CREW

3.1	Nationality of Master:		Turkish
3.2	Number and nationality of Officers:	9	Turkish
3.3	Number and nationality of Crew:	17	Turkish
3.4	What is the common working language onboard:		Turkish, English
3.5	Do officers speak and understand English?		Yes
3.6	If Officers/ratings employed by a manning agency - Full style:	Officers: N/A	Ratings: N/A

### 4. FOR USA CALLS

4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coast Guard which has been approved by official USCG letter?	No
4.2	Qualified individual (QI) - Full style:	Mr. Michael Minogue ECM Maritime Services 1 Selleck Street 5th Floor - Suite 511 Norwalk, CT 06855, USA Tel: +1-203-857-0444 Fax: +1-203-857-0428 Email: QI@ecmmaritime.com
4.3	Oil Spill Response Organization (OSRO) - Full style:	Marine Spill Response Corporation 220 Spring Street, Suite 500 Herndon, VA 20170 Tel: +1-800-259-6772 or + Fax: +1-703-326-5660
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:	

### 5. SAFETY/HELICOPTER

5.1	Is the vessel operated under a Quality Management System? If Yes, what type of system? (ISO9001 or IMO Resolution A.741(18) as amended):	Yes IMO Resolution A.741(18)
5.2	Can the ship comply with the ICS Helicopter Guidelines?	Yes
5.2.1	If Yes, state whether winching or landing area provided:	Landing
5.2.2	If Yes, what is the diameter of the circle provided:	13 Metres

### 6. COATING/ANODES

6.1	Tank Coating	Coated	Type	To What Extent	Anodes
	Cargo tanks:	Yes	High Solid Epoxy - Chugoku - BANNOH 1500	Deckhead with complete internal structure, including brackets connecting to longitudinal and transverse bulkheads. In tanks	No

				with ring frame girder construction, the underdeck transverse framing down to level of the first tripping bracket. Longitudinal and transverse bulkhead down to uppermost means of access level & Bottom to 0.5m upwards	
	Ballast tanks:	Yes	Epoxy	Fully	Yes
	Slop tanks:	Yes	PURE EPOXY	Whole Tank	Yes

<b>7.</b>	<b>BALLAST</b>				
7.1	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Ballast Pumps:	2	Centrifugal	2,750 Cu. Metres/Hour	35 Metres
	Ballast Eductors:	1	TEAMTEC	300 Cu. Metres/Hour	25 Metres

<b>8.</b>	<b>CARGO</b>				
<b>Double Hull Vessels</b>					
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:			Yes, Solid	
<b>Cargo Tank Capacities</b>					
8.2	Number of cargo tanks and total cubic capacity (max% per company policy: 98%, 97%, 96% or 95%) excluding slops tanks:			12	171,383.17 Cu. Metres
8.2.1	Capacity (98%) of each natural segregation with double valve (specify tanks):			1 SEG = 1P&S +4P&S = 53,132.85 2 SEG = 2P&S +5P&S = 59,821.94 3 SEG = 3P&S +6P&S = 58,428.38	
8.2.2	IMO class (Oil/Chemical Ship Type 1, 2 or 3):			1	
8.3	Number of slop tanks and total cubic capacity (98%):			2	3,617.58 Cu. Metres
8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:			3 SEG	
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:			174.70 Cu. Metres	
<b>SBT Vessels</b>					
8.3.3	What is total SBT capacity and percentage of SDWT vessel can maintain?			51,224.70 Cu. Metres	34 %
8.3.4	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:			Yes	
<b>Cargo Handling and Pumping Systems</b>					
8.4	How many grades/products can vessel load/discharge with double valve segregation:			3	
8.5	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:			Yes 1,025kg/lit cargo density	
8.6	Max loading rate for homogenous cargo			With VECS	Without VECS
	Loaded per manifold connection:			7,720 Cu. Metres/Hour	7,720 Cu. Metres/Hour
	Loaded simultaneously through all manifolds:			17,000 Cu. Metres/Hour	17,000 Cu. Metres/Hour
<b>Cargo Control Room</b>					
8.7	Is ship fitted with a Cargo Control Room (CCR)?			Yes	
8.8	Can tank innage/ullage be read from the CCR?			Yes	
<b>Gauging and Sampling</b>					
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:			Yes,	
	What type of fixed closed tank gauging system is fitted:			Radar beam type level gauge	
	Are high level alarms fitted to the cargo tanks? If Yes, indicate whether to all tanks or partial:			Yes, All	
8.9.1	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6?			Yes	
8.9.2	Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:			Yes, 3 vapour locks, 1 each aft, mid and forward	

8.10	Number of portable gauging units (example- MMC) on board:			2	
<b>Vapor Emission Control System (VECS)</b>					
8.11	Is a vapour return system (VRS) fitted?			Yes	
8.12	Number/size of VECS manifolds (per side):			2	406.40 Millimetres
8.13	Number/size/type of VECS reducers:			2x20x12"	
<b>Venting</b>					
8.14	State what type of venting system is fitted:			VENT RISER + HIGH VELOCITY PV VALVES	
<b>Cargo Manifolds and Reducers</b>					
8.15	Total number/size of cargo manifold connections on each side:			3/600 Millimetres	
8.16	What type of valves are fitted at manifold:			Butterfly	
8.17	What is the material/rating of the manifold:			ERWS38/150	
8.17.1	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?			Yes	
8.18	Distance between cargo manifold centers:			2,500 Millimetres	
8.19	Distance ships rail to manifold:			4,600 Millimetres	
8.20	Distance manifold to ships side:			4,600 Millimetres	
8.21	Top of rail to center of manifold:			730 Millimetres	
8.22	Distance main deck to center of manifold:			2,100 Millimetres	
8.23	Spill tank grating to center of manifold:			900 Millimetres	
8.24	Manifold height above the waterline in normal ballast/at SDWT condition:			19.29 Metres	9.60 Metres
8.25	Number/size/type of reducers:			6 x 609.6/406.4mm (24/16") 3 x 609.6/304.8mm (24/12") 3 x 609.6/254mm (24/10") 3 x 609.6/203.2mm (24/8") 2 x 609.6/508mm (24/20") ANSI	
8.26	Is vessel fitted with a stern manifold? If yes, state size:			No,	
<b>Heating</b>					
8.27	Cargo/slop tanks fitted with a cargo heating system?		Type	Coiled	Material
	Cargo Tanks:		STEAM	Yes	SS
	Slop Tanks:		STEAM	Yes	STPG 370S (Carbon Steel)
8.28	Maximum temperature cargo can be loaded/maintained:			66.0 °C / 150.8 °F	66 °C / 150.8 °F
8.28.1	Minimum temperature cargo can be loaded/maintained:				
<b>Inert Gas and Crude Oil Washing</b>					
8.29	Is an Inert Gas System (IGS) fitted/operational?			Yes/Yes	
8.29.1	Is a Crude Oil Washing (COW) installation fitted/operational?			Yes/Yes	
8.30	Is IGS supplied by flue gas, inert gas (IG) generator and/or nitrogen:			Flue Gas	
<b>Cargo Pumps</b>					
8.31	How many cargo pumps can be run simultaneously at full capacity:			3	
8.32	Pumps	No.	Type	Capacity	At What Head (sg=1.0)
	Cargo Pumps:	3	Centrifugal	4000 M3/HR	135 Meters 135 Meters 135 Meters
	Cargo Eductors:	2	Liquid jet Pump	470 Cu. Metres/Hour	25 Metres
	Stripping:	1	Reciprocating	250 Cu. Metres/Hour	135 Metres
8.33	Is at least one emergency portable cargo pump provided?				

<b>9.</b>	<b>MOORING</b>					
9.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:			N/A		
	Main deck fwd:			N/A		
	Main deck aft:	2	36 Millimetres	N/A	240 Metres	85 Metric Tonnes
	Poop deck:	6	36 Millimetres	N/A	240 Metres	85 Metric Tonnes
9.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength

	Forecastle:	4	50 Millimetres	PES/PP mixed yarn [50/50%]	11 Metres	109.10 Metric Tonnes
	Main deck fwd:	4	50 Millimetres	PES/PP mixed yarn [50/50%]	11 Metres	109.10 Metric Tonnes
	Main deck aft:	2	50 Millimetres	PES/PP mixed yarn [50/50%]	11 Metres	109.10 Metric Tonnes
	Poop deck:	6	50 Millimetres	PES/PP mixed yarn [50/50%]	11 Metres	109.10 Metric Tonnes
9.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	31 Millimetres	Dyneema® SK-78 yarns	280 Metres	85.20 Metric Tonnes
	Main deck fwd:	4	31 Millimetres	Dyneema® SK-78 yarns	280 Metres	85.20 Metric Tonnes
	Main deck aft:	2	31 Millimetres	Dyneema® SK-78 yarns	280 Metres	85.20 Metric Tonnes
	Poop deck:	6	31 Millimetres	Dyneema® SK-78 yarns	280 Metres	85.20 Metric Tonnes
9.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	72 Millimetres	POLYPROPELENE	220 Metres	86 Metric Tonnes
	Main deck fwd:					
	Main deck aft:					
	Poop deck:	4	72 Millimetres	POLYPROPELENE	220 Metres	86 Metric Tonnes
9.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Double Drums	Hydraulic	68.20 Metric Tonnes	Band brake
	Main deck fwd:	2	Double Drums	Hydraulic	68.20 Metric Tonnes	Band brake
	Main deck aft:	1	Double Drums	Hydraulic	51.10 Metric Tonnes	Band brake
	Poop deck:	3	Double Drums	Hydraulic	51.10 Metric Tonnes	Band brake
9.6	Bits, closed chocks/fairleads		No. Bits	SWL Bits	No. Closed Chocks	SWL Closed Chocks
	Forecastle:		5	92 Metric Tonnes	8	92 Metric Tonnes
	Main deck fwd:		7	92 Metric Tonnes	9	92 Metric Tonnes
	Main deck aft:		3	92 Metric Tonnes	7	92 Metric Tonnes
	Poop deck:		7	92 Metric Tonnes	13	92 Metric Tonnes
<b>Anchors/Emergency Towing System</b>						
9.7	Number of shackles on port/starboard cable:				14/13	
9.8	Type/SWL of Emergency Towing system forward:				DHF7000-001	350 Metric Tonnes
9.9	Type/SWL of Emergency Towing system aft:				DHA4000-001	204 Metric Tonnes
9.10.1	What is size of closed chock and/or fairleads of enclosed type on stern				600x450	
<b>Escort Tug</b>						
9.10.2	What is SWL of closed chock and/or fairleads of enclosed type on stern:				204 Metric Tonnes	
9.11	What is SWL of bollard on poop deck suitable for escort tug:				204 Metric Tonnes	
<b>Lifting Equipment/Gangway</b>						
9.12	Derrick/Crane description (Number, SWL and location):				Cranes: 1 x 20 Tonnes 2 x 8 Tonnes provision crane	
9.13	Accommodation ladder direction:				Aft	
	Does vessel have a portable gangway? If yes, state length:					
<b>Single Point Mooring (SPM) Equipment</b>						
9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)'?				Yes	
9.15	If fitted, how many chain stoppers:				2	
9.16	State type/SWL of chain stopper(s):				TONGUE SM490	350 Metric Tonnes
9.17	What is the maximum size chain diameter the bow stopper(s) can handle:				76 Millimetres	
9.18	Distance between the bow fairlead and chain stopper/bracket:				3.10 Metres	
9.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:				Yes	

<b>10.</b>	<b>PROPULSION</b>		
10.1	Speed		Maximum Economical
	Ballast speed:	14.50 Knots (WSNP)	12.50 Knots (WSNP)
	Laden speed:	14.50 Knots (WSNP)	12.50 Knots (WSNP)
10.2	What type of fuel is used for main propulsion/generating plant:	VLSFO, ULSFO, LSMGO	VLSFO, ULSFO, LSMGO
10.3	Type/Capacity of bunker tanks:	Fuel Oil: 3,358.50 Cu. Metres Diesel Oil: Gas Oil: 683.20 Cu. Metres	
10.4	Is vessel fitted with fixed or controllable pitch propeller(s):	None	
10.5	Engines	No	Capacity Make/Type
	Main engine:	1	13,900 Kilowatt HYUNDAI MAN B&W 5G70ME-C9.5
	Aux engine:	3	4,170 Kilowatt 2 x Hyundai HIMSEN 7H21/32 and 1 x 6H21/32
	Power packs:		
	Boilers:	2	35 Metric Tonnes/Hour AALBORG OM
<b>Bow/Stern Thruster</b>			
10.6	What is brake horse power of bow thruster (if fitted):	No,	
10.7	What is brake horse power of stern thruster (if fitted):	No,	
<b>Emissions</b>			
10.8	Main engine IMO NOx emission standard:	Tier II	
10.9	Energy Efficiency Design Index (EEDI) rating number:	2.6	

<b>11.</b>	<b>SHIP TO SHIP TRANSFER</b>		
11.1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquefied Gas, as applicable)?	Yes	
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	8 Metres	
11.3	Date/place of last STS operation:	27.05.2020 / KALAMATA	

<b>12.</b>	<b>RECENT OPERATIONAL HISTORY</b>		
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):		
12.2	Has vessel been involved in a pollution, grounding, serious casualty, unscheduled repair or collision incident during the past 12 months? If yes, provide details:	Pollution: No, n/a Grounding: No, n/a Casualty: No, n/a Repair: No, Collision: No, n/a	
12.3	Date and place of last Port State Control inspection:	Jul 06, 2020 / NOVOROSSISK	
12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No n/a	
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: <i>* "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.</i>	ENOC, REPSOL, STASCO, ADNOC, SARAS	
12.6	Date/Place of last SIRE inspection:	Apr 24, 2020 / TRIESTE / ITALY	
12.7	Additional information relating to features of the ship or operational characteristics:		

Revised 2018 ([INTERTANKO/Q88.com](http://www.intertanko.com))

Form completed on <http://www.q88.com/integration.aspx> Please email [support@q88.com](mailto:support@q88.com) an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee.